

# EXHAUST ASSEMBLY PASTE

SEALS JOINTS IN EXHAUST SYSTEMS AND LUBRICATES JOINTS DURING FITTING.

## PRODUCT SHEET

Pack sizes – 140g tubes & 500g cartridges

Hylomar Exhaust Assembly Paste is a water based, heat curing product. It has been specifically designed for use with exhaust systems for automotive and other general applications. The exhaust paste formulation will withstand both pressure and temperatures typically found in vehicle exhaust systems. Hylomar Exhaust Assembly Paste lubricates joints to make assembly easier and faster.

### Typical Applications:

- + For use as an exhaust assembly compound



## FEATURES

- + Water based
- + Heat curing
- + Specifically designed for use in the assembly of exhaust systems for automotive and other general applications
- + Asbestos free
- + Withstand high temperature and pressure

## INSTRUCTIONS FOR USE

Ensure the surfaces to be joined are clean and free of loose rust, dirt and grease. Abrade the surface with medium emery paper. Spread the paste liberally to all joints in the system and assemble the joint immediately after application.

Run the engine at low speed until warm and the paste will set to form a gas tight seal.

**CAUTION: Avoid running engines in confined spaces.**

## TYPICAL PHYSICAL PROPERTIES

Appearance	Light Brown/Beige
Specific Gravity @ 20°C (68°F) (ASTM D4659)	1.89
Service Temperature	Up to 1000°C (1832°F)

### Hylomar Limited

Hylo House, Cale Lane, Wigan, WN2 1JT, UK | Tel: +44 (0)1942 617000 | Fax: +44 (0)1942 617001

### Hylomar GmbH

Talstraße 106, 41516 Grevenbroich, Deutschland | Tel: +49 (0)2182 570 8971 | Fax: +49 (0) 2182 5708970

### Hylomar LLC

158 J J Lane, Center Point, Texas 78010, USA | Tel: +1 830 634 2603